

GSX9000™ High-Density Media Gateway

Circuit Network Server 85 (CNS85) 3 Port T3 Module
with Compression

The Ribbon Communications' CNS85 module processes circuit-based traffic on the Ribbon GSX9000 high-density media gateway. A single CNS85 module supports up to 2,016 DS0s. The CNS85 also supports optional codec-based compression. Each module features a redundant failure configuration and is hot-swappable for live upgrades without service disruption or scheduled downtime.

Call Capacity

- Up to 2,016 DS0s (3 x DS3)

Interface Options

- Three (3) Rx and three (3) Tx 75 ohm BNC coax connectors

Framing

- T3
- M13
- C-bit
- T1
- D4/SF
- ESF
- E1
- MF
- MF-CRC

Line Coding

- B3Zs

Standards

- ANSI
- T1.102
- T1.107
- T1.403
- T1.404

Management Interface

- RS-232 Serial Asynchronous Management Port

Redundancy

- N:1 server redundancy

Status Indicators

- Module Indicators
- Power
- Status
- Activity
- Fault
- Redundancy



- T3 Indicators
- Status: Port is connected and passing frames
- RAI: T3 is receiving yellow alarm
- Red: T3 is receiving red alarm (out of frame)

Channel Hunting

- Circular Sequential
- Backward Circular Sequential
- Most Idle
- Least Idle
- Top to Bottom
- Bottom to Top
- High to Low
- Low to High

Tones and Announcements

- ISUP Continuity Test Tones
- Long Digit Detection
- DTMF/MF Collection and Generation
- Call Progress Generation and Detection
- Announcement Support

Environmental

- Operating Temperature: 5° to 40° C
- Short-Term Operating Temperature: -5° to 55° C
- Non-Condensing Operating Humidity: 5% to 90%

Voice Handling

- G.711 (A/u-law) via RTP or AAL1 Encapsulation
 - RTP Packet Sizes: 10 to 40ms in 5ms Increments
 - RTCP
- G.168 Echo Cancellation up to 128ms
- Silence Suppression
- Comfort Noise Generation
- Adaptive Jitter Compensation with Packet Re-Ordering
- Fixed Gain Control
- Optional Codecs
 - Type 1: G.729A+B, G.726, T.38 fax relay
 - Type 2: Same as Type 1, G.723.1A, ice

- 100% Universal XPAD–Type 1
 - Codec Channels: 2016
 - TPADS: 500
 - BPADS: 225
- 100% Universal XPAD–Type 2
 - Codec Channels: 1620
 - TPADS: 500
 - BPADS: 225
- TPAD – Tone processing
- BPAD – Bridge conferencing

Power

- Nominal Consumption: 1.4 Amps
- Peak Consumption: 1.7 Amps

Weight

- 5.0 lbs

About Ribbon

Ribbon Communications (Nasdaq: RBBN) delivers communications software, IP and optical networking solutions to service providers, enterprises and critical infrastructure sectors globally. We engage deeply with our customers, helping them modernize their networks for improved competitive positioning and business outcomes in today's smart, always-on and data-hungry world. Our innovative, end-to-end solutions portfolio delivers unparalleled scale, performance, and agility, including core to edge software-centric solutions, cloud-native offers, leading-edge security and analytics tools, along with IP and optical networking solutions for 5G. We maintain a keen focus on our commitments to Environmental, Social and Governance (ESG) matters, offering an annual Sustainability Report to our stakeholders. To learn more about Ribbon, please visit rbbn.com.

Contact Us

We are here to help. Let us know if you are interested in a quote or if you have any questions.

Microsoft Partner

Gold Communications

Voice
Unified Communications
Business Productivity Solutions
Midmarket Solution Provider

Copyright © 2022, Ribbon Communications Operating Company, Inc. ("Ribbon"). All Rights Reserved. v0422