

SBC 7000™



Service providers and large enterprises are facing a torrent of demand for multimedia communications applications across global markets. The Ribbon SBC 7000 is a purpose-built session border controller with industry-leading performance and scale that deliver increased operational efficiency and uncompromised quality of service to help securely and efficiently handle and monetize the massive amount of audio, video and collaboration traffic crossing their networks. The SBC 7000 not only provides the critical features service providers and large enterprises equate with Ribbon Session Border Controllers (robust security, sophisticated routing and policy management, overload controls and SIP normalization), it also delivers IPv4-IPv6 interworking, high density media transcoding, and sophisticated policy at high performance levels to meet the increasing demands of multimedia communications. To further simplify deployment, the SBC 7000 implements a fully modular chassis design, enabling service providers and large enterprises to rapidly scale today's networks while preparing for future growth.

System Capabilities

- Sessions
 - 150,000 simultaneous sessions
 - Up to 130,000 transcoded sessions based on codec
 - Up to 32,000 H.323 call legs
 - RTCP sessions scale 1:1 with RTP sessions
 - 40,000 Trunk Groups per system
 - 4096 VLANs
 - Up to 64,000 recording sessions
- Call Set-Up Maximum call setup rate: 1350 cps
- Call latency = 30ms (@ 1350 cps)
- Registrations
 - Maximum new registrations/sec: 2,500
 - Maximum refreshes/sec: 20,000
 - Total registered end point support: 2,000,000
- Encryption
- Maximum number of TLS sessions: 765,000
- TLS set-up rate: 2000/sec
- Maximum # of IPsec tunnels: 4096
- Maximum # SRTP call legs: 300,000
- Maximum # of registered subscribers on IPsec – IMS AKA: 1,000,000

Media Services

- Transcoding G.711, G.726, G.729A/B, G.723, iLBC, G.722, G.722.1, AMR-NB, AMR-WB, EVRCB0, EVRC0, Opus, SILK, EVS
- Wireline, wireless, wideband and clear channel codec pass through
- T.38 compliant fax relay or fall back to G.711
- VAD, silence suppression, dynamic jitter buffer, fax/modem detection, DTMF/tone relay/RFC2833/RFC4733 interworking
- Message Session Relay Protocol (MSRP) - MSRP B2BUA and MSRP-CEMA



▶ [Click Here to Get a Quote for One of Our SBCs](http://rbbn.com/ribbon-sbc-quote)
<http://rbbn.com/ribbon-sbc-quote>

- NAT/NAPT on media DTMF trigger detection and notification
- Generic audio codec relay
- Tones & announcements
- Local Ring Back Tone (LRBT) support with centralized PSX Policy Server
- RTP inactivity monitoring
- Supported video codecs: H.264 AVC, H.264 SVC, H.263+, H.263, H.261, VP8
- Support up to 4 simultaneous SIPREC recordings per session

Redundancy

- 1:1 redundant systems for service availability
- 1:1 redundant management/control ports
- 1:1 redundant media ports

Management Capabilities

- Graphical based wizards for ease of configuration
- Secure embedded web-based management GUI
- Ribbon CLI, SSH
- Representational State Transfer (REST) API
- Centralized support by Ribbon Insight EMS
- SNMP V2/V3 status and statistics
- Local logging of events, alarms, traps, and call traces
- Ribbon DSI Level 0 support for storing CDRs, RADIUS accounting records
- Live software update (LSWU)
- Real time streaming of RTCP statistics for Ribbon Analytics
- APIs for call notification event and call termination

Signaling

- Back to back user agent (B2BUA)
- SIP, SIP-I/SIP-T, SIP/H.323, Ribbon gateway to gateway protocol
- SIP protocol normalization/protocol repair, SIP message manipulation
- NAT/NAPT on signaling
- Binary floor control protocol (BFCP)
- Far-end camera control (FECC)

Protocol Support

- IPv4, IPv6, IPv4/IPv6 interworking
- SSH, SRTP
- SNMP, NTP
- HTTP/HTTPS
- RTP/RTCP
- UDP, TCP
- DNS, ENUM
- DTLS - SRTP
- ICE - STUN

Routing/Policy

- Embedded policy/routing engine
- Centralized support with Ribbon PSX using DIAMETER+
- Screening, blocking, routing, presentation, call type filters
- Route prioritization
- Leading digit routing, international routing, URI based routing
- Digit/parameter manipulation
- E911 support, priority call handling
- Locally survivable session mode when registrar is not reachable
- Routing based on Active Directory lookup

Security

- Session aware firewall, topology hiding
- Line rate DoS/DDoS and rogue RTP protection
- Line rate malformed packet protection
- TLS, IPSec (IKEv1) for signaling encryption
- Secure RTP/RTCP for media encryption
- Support for STIR/SHAKEN Caller ID Authentication and Verification

Certifications

- Microsoft Skype for Business and Lync 2013
- Microsoft Direct Routing including media bypass
- BroadSoft BroadWorks Platform

Quality of Service (QoS)

- Bandwidth management
- Call admission control (CAC) per trunk group, per zone
- Per call statistics
- TOS/COS packet marking

Packet Network Time Source

- Network Time Protocol (NTP) per RFC-1708

Hardware Specifications

Front Panel

- Status Indicators Front Panel LEDs:
- Status
- Alarm
- Active
- Locator
- Power
- Single USB V2.0 interface

Rear Panel

- Management Ports:
 - Two GigE Ethernet ports (RJ-45, SFP-LC-MM, SFP-LC-SM)
- Media Ports:
 - Four 10 Gbps Ethernet fiber (SFP-LC-MM, SFP-LC-SM)
- High Availability Ports:
 - Two 10 Gbps Ethernet fiber via SFP
- Single Field Service port with RJ45 connector
- Locator LED
- Alarm port with DB15 connector
- Single serial craft DB9 port

DSP Expansion

- Modular DSP slots

Chassis

- 5U rack mount
- Inches: 17" wide x 8.75" high x 23" deep
- Centimeters: 43.2cm wide x 22.2cm high x 58.4cm deep
- Replaceable filter

Chassis Mounting Options

- 19" or 23" adjustable brackets

AC Power Option

- Maximum Current: 15.0 A
- RMS input voltage
- Minimum 180 VAC
- Nominal 200-240 VAC
- Maximum 264 VAC

- Input frequency
- Minimum 47 Hz
- Nominal 50/60 Hz
- Maximum 63 Hz

DC Power Option

- Maximum Current: 62 A
- DC Input Range
 - Maximum 60 VDC
 - Nominal 48 VDC
 - Minimum 40 VDC

Operating Altitude

- 6,000 feet
- 1,800 meters

Heat Dissipation

- Fully-populated maximum:
 - 2900 Watts

Weight Maximum Fully Populated

- 98 lbs. (44.4kg)

Environmental

- 5 to 40° C operating
- -5 to 55° C short term
- 5 to 90% non-condensing operating humidity

Regulatory Compliance

Central Office Standards

- DC Systems – SR-3580 NEBS Level 3
- GR-1089-CORE
- GR-63-CORE
- AC Systems – SR-3580 NEBS Level 3
- GR-1089-CORE
- GR-63-CORE

Configuration	AC Low Line (W)		DC Input (W)	
	Amps	Watts	Amps	Watts
SBC7000 - No DSP Cards	7	1217	23	938
SBC7000 + 1 x DSP	9	1571	33	1326
SBC7000 + 2 x DSP	11	1940	42	1679
SBC7000 + 3 x DSP	13	2326	51	2059
SBC7000 + 4 x DSP	15	2724	62	2473

Table 1. Estimated Power Consumption

► [Click Here to Get a Quote for One of Our SBCs](http://rbbn.com/ribbon-sbc-quote)
<http://rbbn.com/ribbon-sbc-quote>

About Ribbon Communications

Ribbon is a company with two decades of leadership in real-time communications. Built on world class technology and intellectual property, Ribbon delivers intelligent, secure, embedded real-time communications for today's world. The company transforms fixed, mobile and enterprise networks from legacy environments to secure IP and cloud-based architectures, enabling highly productive communications for consumers and businesses. With locations in 28 countries around the globe, Ribbon's innovative, market-leading portfolio empowers service providers and enterprises with rapid service creation in a fully virtualized environment. The company's Kandy Communications Platform as a Service (CPaaS) delivers a comprehensive set of advanced embedded communications capabilities that enables this transformation.

To learn more visit RibbonCommunications.com

Microsoft Partner
Gold Communications

Voice
Unified Communications
Business Productivity Solutions
Midmarket Solution Provider